



Component - Plastics

DOMO ENGINEERING PLASTICS EUROPE SPA
VIA LINFANO 18
ARCO, TN 38062 Italy



(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

NOTE - - Materials designated "Technyl" may be prefixed by the letters "TY". Optional color name (in letters) followed by 1 to 10 alphanumeric code. Materials with codes ending with letter "D" alone are not UL Recognized

Flammability	Value	Test Method
Flame Rating		UL 94
0.75 mm, NC, RD, BK	V-0	IEC 60695-11-10, -20
1.5 mm, NC, RD, BK	V-0	
3.0 mm, NC, RD, BK	V-0	
Glow Wire Ignition Temperature (1.5 mm)	825 °C	IEC 60695-2-13
Thermal	Value	Test Method
RTI Elec		UL 746B
0.75 mm	65.0 °C	
1.5 mm	65.0 °C	
3.0 mm	65.0 °C	
RTI Imp		UL 746B
0.75 mm	65.0 °C	
1.5 mm	65.0 °C	
3.0 mm	65.0 °C	
RTI Str		UL 746B
0.75 mm	65.0 °C	
1.5 mm	65.0 °C	
3.0 mm	65.0 °C	
Physical	Value	Test Method
Outdoor Suitability	f1	UL 746C